



TRVN 40- 70 / 1 - C - M / A3 - Z1

Pompetravaini Construction

Liquid ring vacuum pumps

Construction type for Medium Vacuum rate

V = Single stage pump with Reed valve
BARESHAFT with CLOSE-COUPLED and Coupling

Hydraulic project index: **N**

Suction and discharge flange DN (mm)

Nominal flow rate m³/h

Construction Project Number

1 = Standard Construction
1W = Construction for Compressor use

Shaft Seal Type

C = No.1 Component Mechanical Seal - Single
C2 = No.1 Component Mechanical Seal - Double back-to-back

Close-coupled construction with Motor Lantern

Material of Construction

A3 = AISI 316 stainless steel construction

Special Executions

Z1 = Suction/Discharge ports and Liquid Supply port with ISO-DIN flanges
Z2 = Suction/Discharge ports and Liquid Supply port with ANSI flanges
Z3 = Suction/Discharge ports and Liquid Supply port with ANSI flanges
Motor Lantern for assembly with NEMA motor.
Z4 = Low magnetic permeability version with two bearings on NDE side.
Z5 = Suction/Discharge ports with ANSI flanges and Liquid Supply port with ANSI thread
Z6 = Suction/Discharge ports with ANSI flanges and Liquid Supply port with ANSI thread
Motor Lantern for assembly with NEMA motor.

RIF. - Ref.: E.C./C.T.

DATA - Date: 10/2025

SOSTITUISCE - Replaces : 9000.871.01.01

N°.: 9000.871.02.01